



Sauer Compressors USA

Sauer Compressors USA, Inc

245 Log Canoe Circle

Stevensville, MD 21666

Phone: 410-604-3142 • **Fax:** 410-604-3209

E-Mail: sales@sauerusa.com • **Web site:** www.sauerusa.com

100 to 580 psi Compressors, Air Cooled (Mistral Series)

The 2-stage air-cooled compressors helped establish Sauer's reputation for high quality. After 75 years of production, these models are now in their third generation of development. These models are designed to have the following advantages: Direct drive (no belt maintenance) Light weight with small installation footprint. Engineered for continuous operation in extreme environments. Extended operation time between required maintenance intervals (2000 operating hours).



1

<u>Item #</u>	<u>Operating Pressure Range</u>	<u>Flow Rate</u>	<u>Required Power</u>	<u>Stages/Cylinders</u>	<u>Gas/Medium</u>
WP15L	150 to 580 psi	5.8 to 9.2 SCFM	3.2 to 5.8 hp	2/2	Air, Nitrogen
WP22L	150 to 580 psi	8.1 to 12.9 SCFM	4.3 to 7.6 hp	2/2	Air, Nitrogen
WP33L	150 to 500 psi	11.2 to 18.4 SCFM	6.2 to 11 hp	2/2	Air, Nitrogen

<u>Item #</u>	<u>Operating Pressure Range</u>	<u>Flow Rate</u>	<u>Required Power</u>	<u>Stages/Cylinders</u>	<u>Gas/Medium</u>
WP45L	150 to 580 psi	20.0 to 35.7 SCFM	8.7 to 16.1 hp	2/2	Air, Nitrogen
WP65L	150 to 580 psi	26.5 to 47.0 SCFM	11.7 to 21.4 hp	2/2	Air, Nitrogen
WP146L	100 to 150 psi	62.4 to 92.3 SCFM	22 to 92.3 hp	2/2	Air, Nitrogen
WP226L	100 to 150 psi	112.5 to 154.3 SCFM	30.4 to 55.7 hp	2/2	Air, Nitrogen