

# Robo-Drain

THE RECOGNIZED  
INDUSTRY LEADER IN  
**RELIABILITY**

Robo-Drain

## FEATURES & BENEFITS

- Fully Automatic - Zero Air Loss
- Featuring standard designs to fit a wide range of compressor sizes
- Discharge amounts range from 24 to 72 ounces
- Uses pilot air, no electricity required
- Low pressure (0-250 PSI) and high pressure (up to 750 PSI) versions available
- Models available for both compressed air and vacuum systems



# Robo-Drain RD11-T



External Pneumatic Condensate Drain

[CLICK HERE TO VIEW ONLINE](#)

SPECIFICATIONS	
Inlets	(2) 3/4" NPT
Outlets	1/2" NPT
Power	Clean, dry compressed air 55 - 130 PSI
Pressure	0 - 250 PSI
Operating Temp.	32° - 180° F
Weight	17 lbs.
Discharge	24 oz. per cycle
Options & Accessories	BSPP Fittings, Heater, Alarm, Stainless Steel Heads and/or Internals, Low Pressure Variant*

MATERIALS	
Reservoir	Aluminum & Composite
Valve	Bronze with S.S. Ball & Stem
Float	Stainless Steel
Seat	Stainless Steel
Seal	Viton®

# Robo-Drain RD13-T



High Capacity External Pneumatic  
Operated Condensate Drain

[CLICK HERE TO VIEW ONLINE](#)

SPECIFICATIONS	
Inlets	(2) 3/4" NPT
Outlets	1/2" NPT
Power	Clean, dry compressed air 55 - 130 PSI
Pressure	0 - 250 PSI
Operating Temp.	32° - 180° F
Weight	22 lbs.
Discharge	72 oz. per cycle
Options & Accessories	BSPP Fittings, Heater, Alarm, Stainless Steel Heads and/or Internals, Low Pressure Variant*

MATERIALS	
Reservoir	Aluminum & Composite
Valve	Bronze with S.S. Ball & Stem
Float	Stainless Steel
Seat	Stainless Steel
Seal	Viton®

**Robo-Drain RD750**



**External Pneumatic Operated High-Pressure  
Condensate Drain**

[CLICK HERE TO VIEW ONLINE](#)

**SPECIFICATIONS**

Inlets	(2) 3/4" NPT
Outlets	1/2" NPT
Power	Clean, dry compressed air 55 - 130 PSI
Pressure	0 - 750 PSI
Operating Temp.	32° - 180° F
Weight	22 lbs.
Discharge	24 oz. per cycle
Options & Accessories	BSPP Fittings, Heater, Alarm

**MATERIALS**

Reservoir	304 Stainless Steel
Valve	Stainless Steel w/ S.S. Ball & Stem
Float	Stainless Steel
Seat	Stainless Steel
Seal	Viton®

**Robo-Drain RD11-VAC**



**External Pneumatic Operated Condensate Drain  
for Vacuum Systems**

[CLICK HERE TO VIEW ONLINE](#)

**SPECIFICATIONS**

Inlets	3/4" NPT
Outlets	1/2" NPT
Power	Clean, dry compressed air 55 - 130 PSI
Pressure	26" Hg vacuum to 90 PSI
Operating Temp.	32° - 180° F
Weight	17 lbs.
Discharge	24 oz. per cycle
Options & Accessories	BSPP Fittings, Heater, Alarm

**MATERIALS**

Reservoir	Aluminum & Composite
Valve	Bronze with S.S. Ball & Stem
Float	Stainless Steel
Seat	Stainless Steel
Seal	Viton®